



Version : 1
Date : June 1th, 2022

SYNTRAX 75W140

Description

Syntrax 75W-140 meets the requirement of Scania STO 1:0 and STO 2:0A. The origin of the product is included in the Scania High Performance product list and is approved against Scania STO 1:0 and STO 2:0A.

The product has excellent properties like:

- Excellent anti-wear and extreme pressure performance at all ambient temperatures and load conditions
- Provides superior protection, longer component life and reduced repair costs.
- Excellent cold flow properties reduce torque loss and increase fuel efficiency
- Improved protection at start up and in cold conditions
- Extended drain capability reduces maintenance costs
- Excellent thermal and oxidative stability
- Protects against pitting
- Excellent shear stability

Application

Syntrax 75W140 is a full synthetic final drive lubricant which is suitable for use in axles and final drives in heavy duty commercial vehicles where API GL-5 performance is required. May also be used in light duty commercial

Specifications

API GL5 | SCANIA STO 1:0 | SCANIA STO 2:0A

Typical Characteristics

Density at 15°C,	kg/l	:	0,870
Kin. viscosity 40 °C,	mm ² /s	:	182
Kin. viscosity 100 °C,	mm ² /s	:	25,0
Viscosity Index		:	170
Flash Point COC,	°C	:	234
Pour Point,	°C	:	-54

UTB B.V.

Mandenmakerstraat 21-25
2984 AS Ridderkerk
The Netherlands

T: +31(0)88 - 0202300
F: +31(0)88 - 0202399

I: www.utb.nl
E: info@utb.nl

Mentioned product values are indicative typical values. UTB BV can not be held responsible for any printing or typographical errors. On all our transactions our general delivery and sales conditions apply. Vermelde productwaarden zijn indicatieve typische waarden. UTB BV kan niet aansprakelijk worden gehouden voor eventuele druk- of zetfouten. Op al onze transacties zijn onze algemene leverings- en verkoopvoorwaarden van toepassing.